

Product Information

HARDENER UT-R 20

Available Quantities:

Product	Contents	Ref. No.
Hardener UT-R 20	20 g	525 1036
	40 g	525 1043

Fields of Application:

Hardener for REMA TIP TOP Cement SC 2000, Cement BC 3000, Plastic Cement and Heating solution WK.

Product Description:

Polymer basis:	Polyisocyanate
Solvent:	Methylene chloride
Colour:	Light brown
Density:	1,30 g/ml
Dosage:	4% of weight of Cement SC 2000, Cement BC 3000 or Plastic Cement

Mixing:

The Hardener UT-R 20 is added to the Cement SC 2000, Cement BC 3000 or Plastic Cement and thoroughly stirred, until cement and hardener are mixed homogeneously (4% = 40g per 1kg of Cement).

Shelf Life:

1 year when storing in unopened original container under storing conditions in accordance with DIN 7716.

Information given in the fact sheet above corresponds to the current knowledge available to us regarding our products at the time of its drafting and is intended as a guideline for informational purposes. However, because of the multiple possibilities regarding possible applications, processing and on site conditions, any information given in the fact sheet above is not legally binding, in particular, without being limited to, such information shall not be interpreted as a warranty of merchantability or of fitness for a particular purpose. Customer therefore is advised to conduct its own testing or make an inquiry with our technical department before ordering.

We reserve the right to change the product at any time, in particular, without being limited to, minor changes because of advancements in technology.

If by way of exception, the information given in the fact sheet above is incorporated by reference into any contract concluded with us under German Law, such information, shall only be interpreted as determining the specific requirements of the contractual products as set out in § 434 BGB (German Civil Code) and shall not be interpreted as constituting a guarantee of condition.